

Technical specifications

Surestep original meets the requirements of EN - ISO 10582 and EN 13845

	Total thickness	EN - ISO 24346	2.0 mm
	Thickness wear layer	EN - ISO 24340	0.7 mm
	Commercial very heavy	EN - ISO 10874	Class 34
	Light industrial	EN - ISO 10874	Class 43
	Roll width	EN - ISO 24341	2.00 m
	Roll length	EN - ISO 24341	20 - 27 m
	Total weight	EN - ISO 23997	2.75 kg/m²
	Dimension stability	EN - ISO 23999	< 0.1%
	Residual indentation	EN - ISO 24343-1	≤ 0.05 mm
	Castor chair	EN 425	No effect
	Use in wet areas	EN 13533	Yes
	Light fastness	EN - ISO 105 B-02	≥6
	Flexibility	EN - ISO 24344	ø 10mm
	Slip resistance	EN 13845 Annex C	ESb / ESf
		EN 13845 Annex D 50.000 revolutions <10% loss	Pass
		DIN 51130	R10
		Din 51097	Class C
	Chemical resistance	EN-ISO 26987	Very good
	Electrical resistance	EN 1081 (R1)	> 1.10⁹ Ω
	Surface finish		PUR Pearl
Surestep original meets the requirements of EN 14041			EN 14041 CE 0200101-DoP-306
	Reaction to fire	EN 13501-1	B _f -s1
	Body voltage	EN 1815	< 2kV
	Thermal conductivity	EN 12524	0.25 W/m·K
	Slip resistance	EN 13893	DS: ≥0.30

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
 All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.
 The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

